

**Selection and Ordering data**

Order No.

**Milltronics TASS Speed Sensor**

Compact, low-profile, wheel driven return belt speed sensor for belt conveyors; ideal for use on mobile crushers and in constricted spaces.

**Model**

5 pulses per revolution

**Fabrication**

Standard, polyester painted mild steel

Stainless steel 304 (1.4301)

Note: Wheel is aluminum for all versions

**Mounting options**

Complete with standard mounting kit

**Approvals**

CE, C-TICK

C) 7MH7131-

0

1

A

B

A

1

**Selection and Ordering data**

Order No.

**Milltronics TASS Speed Sensor**

Compact, low-profile, wheel driven return belt speed sensor for belt conveyors; ideal for use on mobile crushers and in constricted spaces.

**Instruction manual**

TASS Instruction Manual, Multi-language

Note: The instruction manual should be ordered as a separate item on the order.

This device is shipped with the Siemens Milltronics manual CD containing the complete instruction manual library.

**Spare parts**

TASS Wheel

TASS Proximity Switch

TASS Wheel, stainless steel sealed bearing

C) 7MH7131-

0

C) 7ML1998-5HL61

7MH7723-1AN

7MH7723-1AP

7MH7723-1GW

C) Subject to export regulations AL: N, ECCN: EAR99