

Selection and ordering data

Order No.

Milltronics BW100

C) **7MH7150-**

An economical integrator for use with belt scales. Standard features include; dual totalizer, analog rate output, alarm relay, linearizer and bi-polar current communications.

Input voltage

AC voltage
12 V DC
24 V DC

1
2
3

Feature software

Standard

A

Data communications

Bi-polar current

1

Enclosures

Standard enclosure, no entry holes
Standard with 4 drilled and tapped M20 entry holes

1
3

Trade approval stickers

No trade approval sticker
Not legal for Canadian and EU trade sticker

0
1

Approvals

CSA_{NRTL/C}, CE (EN 61326), FM, C-TICK

D

Further designs

Please add "-Z" to Order No. and specify Order code(s).

Order Code

Stainless Steel tag (69 mm x 50mm)
Measuring-point number / identification
(max 16 characters), specify in plain text.

Y15

Painted mild steel, anti-vibration enclosure with viewing window (finished unit is mounted inside enclosure)] 406 x 305 x 203 mm (16" x 12" x 8"), Type 4X, IP66

A16

Instruction manuals

English
German
French
Spanish

Order No.
C) **7ML1998-5DJ02**
C) **7ML1998-5DJ31**
C) **7ML1998-5DJ11**
C) **7ML1998-5DJ21**

Note: The instruction manual should be ordered as a separate item on the order.

Additional instruction manuals

LVDT Conditioner Card Manuals, English
LVDT Conditioner Card Manuals, German

C) **7ML1998-5EF01**
C) **7ML1998-5EF31**

This device is shipped with the Siemens Milltronics manual CD containing the complete instruction manual library.

Optional equipment

LVDT Conditioners in Nema 4 enclosure (to interface LVDT belt scale without internal pre-amplifier)
SITRANS RD100 Remote displays - see RD100 on page 7/100
SITRANS RD200 Remote displays - see RD200 on page 7/102

C) **7MH7723-1AJ**

C) Subject to export regulations AL: N, ECCN: EAR99