Selection and ordering data	Order No.
Milltronics SF500 C)	7MH7156-
A full feature, powerful integrator designed for use with solids flowmeters	
Input voltage AC voltage	1
Auxiliary input/output boards ¹⁾	
None	A
Board with 2 analog inputs and 2 analog outputs	В
Feature software Standard	A
Auxiliary memory	
None	0
Data communications ²⁾	
SmartLinx® Ready	0
Smartlinx A-B® RIO module	1
Smartlinx PROFIBUS DP module	2
Smartlinx DeviceNet [™] module	3
Enclosures	
Standard enclosure, no entry holes	1
Standard enclosure, 4 entries, M20	2
Trade approval stickers	
No trade approval sticker Not legal for Canadian and EU trade sticker	A
Ŭ	
Approvals CE, CSAus/c, FM, C-TICK	A
Further designs	Order Code
Please add "-Z" to Order No. and specify Order code(s).	
Stainless Steel tag (69 mm x 50 mm),	Y15
Measuring-point number/identification (max 16 characters), specify in plain text.	
Stainless steel enclosure, 304 (1.4301),	
[406 x 305 x 152 mm (16" x 12" x 6"), Type 4X, IP66	
(finished unit is mounted inside enclosure)]	
With window	A11
Without window	A12
Painted mild steel, [406 x 305 x 152 mm	
(16" x 12" x 6"), Type 4X, IP66 (finished unit is	
mounted inside enclosure)]	
With window	A13
Without window	A14
Painted mild steel, anti-vibration enclosure with viewing window (finished unit is mounted inside	A16
enclosure)] 406 x 305 x 203 mm (16" x 12" x 8"), Type 4X, IP66	
1)	

Required for PID control and online calibration.
Required for industrial communications.

C) Subject to export regulations AL: N, ECCN: EAR99

Selection and ordering data		Order No.
Instruction manuals SF500, English SF500, French SF500, German Note: The instruction manual should be ordered as a separate item on the order.	C)	7ML1998-5CN02 7ML1998-5CN11 7ML1998-5CN31
Additional instruction manuals Smartlinx Allen-Bradley® Remote I/O, English	C)	7ML1998-1AP03
Smartlinx PROFIBUS DP, English Smartlinx PROFIBUS DP, German Smartlinx PROFIBUS DP, French	C)	7ML1998-1AQ03 7ML1998-1AQ33 7ML1998-1AQ12
Smartlinx DeviceNet [™] , English Note: The appropriate Smartlinx instruction manual should be ordered as a separate line on the order.	C)	7ML1998-1BH02
LVDT Conditioner Card Manuals, English LVDT Conditioner Card Manuals, German		7ML1998-5EF01 7ML1998-5EF31
This device is shipped with the Siemens Milltronics manual CD containing the complete instruction manual library.	;	
Optional equipment Milltronics analog I/O cards LVDT Conditioners in NEMA 4 enclosure (to interface LVDT belt scale without internal pre- amplifier) SITRANS RD100 Remote displays - see RD100 on page 7/100 SITRANS RD200 Remote displays see RD200 on page 7/102		7MH7723-1BJ 7MH7723-1AJ
Spare parts Displays Lids with overlay and keypad Motherboards		7MH7723-1AF 7MH7723-1AG 7MH7723-1AH
Batteries, 3V, lithium Fuses, 2A, 250V, BW500/SF500, spare LVDT conditioners in NEMA 4 enclosure	Ć)	7MH7723-1ES 7MH7723-1DG 7MH7723-1AJ
Auxiliary I/O cards spare Cables to connect BW500/SF500 keypad to moth- erboard	C)	7MH7723-1BJ 7MH7723-1CB
Keypads spare for BW500/SF500		7MH7723-1CD

C) Subject to export regulations AL: N, ECCN: EAR99