Pointek Specials ¹⁾			Pointek Specials ¹⁾		
	Order N	No.			Order No.
CLS100 Polycarbonate Lid and Gasket, FKM			Kit, Sensor for cable units, PVDF, Standard, FFKM	C)	A5E01163683
			Kit, Sensor for cable units, PVDF, Digital, FFKM	C)	A5E01163684
		\bigcirc	CLS200 Mounting Bracket, 316L stainless steel		A
Kit, Lid and gasket, CLS100 enclosure version	⁻) A5E01	163671	Sicci		
CLS100 Miscellaneous Parts					\leq \backslash
Custom length of cable is available only for 7ML5501-xxx1x and 7ML5501-xxx5x	2)				
CLS200 Gasket (IP65), Synprene			Spare mounting bracket		A5E01163685
			CLS200 PROFIBUS Connector (IP65)		
			Spare, PROFIBUS connector (IP65 versions only)		A5E01163686
		100070	CLS200 Miscellaneous Parts		
Spare gasket, enclosure version I (IP65 versions only)	A5E01 ⁻	163672	CLS200 with FFKM O-rings (any version)		2)
			CLS200 Electronics		
			Test magnet, digital version	\sim	7ML1830-1JE
	<u> </u>		Amplifier/power supply kit, standard version Amplifier/power supply, digital version		A5E03251681 7ML1830-1JF
			LCD display, digital version	L)	7ML1830-1JK
			CLS300 Cable Extensions, 316L stainless		
CLS200 Gasket (IP68), Silicone			steel		
			Kit, Stainless steel cable extension, 1 m, adjustable by customer		A5E01163688
(IP68 versions)	E) A5E01	163673	Kit, Stainless steel cable extension, 3 m, adjustable by customer		A5E01163689
CLS200 Blind Lid		\mathcal{I}	Kit, Stainless steel cable extension, 5 m, adjustable by customer		A5E01163690
			Kit, Stainless steel cable extension, 10 m, adjustable by customer		A5E01163691
		\bigcirc	Kit, Stainless steel cable extension, 15 m, adjustable by customer		A5E01163693
Spare aluminum blind lid (for standard versions only)	A5E01	163674	Kit, Stainless steel cable extension, 20 m, adjustable by customer		A5E01163695
CLS200 Lid with window	45501	100070	CLS300 Cable Extensions, 316 stainless steel with PFA coating		Ť
Spare aluminum lid with window CLS200 Sensor Kit for cable units	ASEUT	163676	·		Đ
CLS200 Sensor Kit for Cable units	P.				
Kit, Sensor for cable units, PPS, Standard,	C) A5E01	163677	Kit, PFA cable extension, 1 m, adjustable by customer Kit, PFA cable extension, 3 m,		A5E01163697 A5E01163698
FKM			adjustable by customer		
Kit, Sensor for cable units, PPS, Standard,	C) A5E01 [·] C) A5E01 [·]		Kit, PFA cable extension, 5 m, adjustable by customer Kit, PFA cable extension, 10 m,		A5E01163699 A5E01163700
FFKM Kit, Sensor for cable units, PPS, Digital, FFKM	C) A5E01	163680	adjustable by customer Kit, PFA cable extension, 15 m,		A5E01163700
	C) A5E01		Adjustable by customer Kit, PFA cable extension, 20 m,		A5E01163701
	C) A5E01	163682	adj.by customer		

Pointek Specials. 1)		Pointek Specials. 1)		
	Order No.	Order No.		
CLS300 Rod Kits, 316L stainless steel		CLS300 Electronics		
Kit, Stainless steel rod 180 mm (7.09") to be used with CLS300 units only (with standard active shield). Insertion length after installa- tion is 350 mm (13.78").	A5E01163719	Test magnet, digital version7ML1830-1JEAmplifier/power supply kit, standard versionC)A5E03251683Amplifier/power supply, digital versionL)7ML1830-1JFLCD display, digital version7ML1830-1JK		
Kit, Stainless steel rod 330 mm (12.99") to be used with CLS300 units only (with standard active shield). Insertion length after installa- tion is 500 mm (19.69").	A5E01163720	CLS300 Weight Kit, 316L stainless steel		
Kit, Stainless steel rod 580 mm (22.83*) to be used with CLS300 units only (with standard active shield). Insertion length after installa- tion is 750 mm (29.53*).	A5E01163721			
Kit, Stainless steel rod 830 mm (32.68") to be used with CLS300 units only (with standard active shield). Insertion length after installa- tion is 1000 mm (39.37").	A5E01163722	Kit, Spare stainless steel weight. To be used A5E01163727 in any cable version of CLS300		
Kit, Stainless steel rod 1330 mm (52.36") to be used with CLS300 units only (with stan- dard active shield). Insertion length after installation is 1500 mm (59.06").	2)	CLS500 Gasket (IP65), Silicone		
Kit, Stainless steel rod 1830 mm (72.05") to be used with CLS300 units only (with stan- dard active shield). Insertion length after installation is 2000 mm (78.74").	2)	Spare gasket, CLS500 enclosure version, J) A5E01163728		
Kit, Stainless steel rod customized length up to 1 m	2)	CLS500 Blind Lid		
Kit, Stainless steel rod customized length up to 2 m CLS300 Electronics Kits with drivers (for rod or cable versions)	2)			
	85	Spare CLS500 aluminum blind lid A5E01163729 CLS500 Electronics Kit		
		Transmitter, MSP 2002-1, 330 PF C) 7ML1830-1JP		
Kit, Electronics with driver, standard CLS300. To be used in rod or cable versions with length less than 5 m. $^{3)}$ $^{4)}$	Please contact <u>nacc smpi@siemens.com</u> for part number and p mit Application Questionnaire found on page 5/9.			
To be used in rod or cable versions with length less than 5 m. $^{3) 4)}$	C) A5E01163725	 ²⁾ Please contact <u>nacc.smpi@siemens.com</u> for part number and pricing. ³⁾ For General Purpose approvals only. ⁴⁾ To maintain approvals, qualified trained Siemens 		
CLS300 Electronics Kits with drivers (for cable versions)	0	 personnel required for part replacement. Please contact <u>nacc.smpi@siemens.com</u> for special requests. C) Subject to export regulations AL: N, ECCN: EAR99. F) Subject to export regulations AL: 91999, ECCN: N. L) Subject to export regulations AL: N, ECCN: 3A991X. J) Subject to export regulations AL: 91999, ECCN: EAR99H. 		
Kit, Electronics with driver, standard CLS300. To be used in cable versions with length greater than 5 m. $^{3)}$ ⁴⁾	C) A5E01163724			
Kit, Electronics with driver, digital CLS300. To be used in cable versions with length greater than 5 m. ^{3) 4)}	C) A5E01163726			