



Process connection part kits - non-pressure-rated	
LR260/LR460, 100 mm extension for horn antenna, no purge ¹⁾	A5E01087872
LR260/LR460, 200 mm extension for horn antenna, no purge ¹⁾	A5E01091262
LR260/LR460, 100 mm extension for horn antenna with purge ¹⁾	A5E01261979
LR260/LR460, 200 mm extension for horn antenna with purge ¹⁾	A5E01261981
LR260/LR460, horn 2", no purge, no emitter ¹⁾	A5E02083905
LR260/LR460, horn 3", no purge, no emitter ¹⁾	A5E01623511
LR260/LR460, horn 4", no purge, no emitter ¹⁾	A5E01623512
LR260/LR460, horn 2", with purge, no emitter ¹⁾	A5E02083906
LR260/LR460, horn 3", with purge, no emitter ¹⁾	A5E01623513
LR260/LR460, horn 4", with purge, no emitter ¹⁾	A5E01623514
LR260/LR460, 3" universal flat faced flange ¹⁾	A5E02303897
LR260/LR460, 4" universal flat faced flange ¹⁾	A5E01259467
LR260/LR460, 6" universal flat faced flange ¹⁾	A5E01261834
LR260/LR460 O-rings for Easy Aimer ¹⁾ F)	A5E01261836
Kit, Emitter for LR260/LR460 ¹⁾	A5E02360694
LR260 lid with O-ring	A5E02465410

Purge conversion kit - non-pressure-rated (no flange or extension included)	
LR260/LR460 purge conversion, 2" horn ¹⁾	A5E02083914
LR260/LR460 purge conversion, 3" horn ¹⁾	A5E02083915
LR260/LR460 purge conversion, 4" horn ¹⁾	A5E02083916

Enclosure with electronics	
	
LR260 enclosure with board stack, HART communication, M20 cable inlet, approval option A, no process connection	C) A5E02203605
LR260 enclosure with board stack, PROFIBUS PA communication, M20 cable inlet, approval option A, no process connection	C) A5E02213423
LR260 enclosure with board stack, HART communication, NPT cable inlet, approval option A, no process connection	C) A5E02165924
LR260 enclosure with board stack, PROFIBUS PA communication, NPT cable inlet, approval option A, no process connection	C) A5E02213428

Enclosure with electronics (LR460)	
	
LR460 enclosure with board stack, HART communication, AC power, M20 cable inlet, approval option A, no process connection	L) A5E02182085
LR460 enclosure with board stack, PROFIBUS PA communication, AC power, M20 cable inlet, approval option A, no process connection	C) A5E02212422
LR460 enclosure with board stack, HART communication, AC power, NPT cable inlet, approval option A, no process connection	L) A5E02212423
LR460 enclosure with board stack, PROFIBUS PA communication, AC power, NPT cable inlet, approval option A, no process connection	L) A5E02212424
LR460 enclosure with board stack, HART communication, DC power, M20 cable inlet, approval option A, no process connection	L) A5E02212425
LR460 enclosure with board stack, PROFIBUS PA communication, DC power, M20 cable inlet, approval option A, no process connection	L) A5E02212426
LR460 enclosure with board stack, HART communication, DC power, NPT cable inlet, approval option A, no process connection	L) A5E02212428
LR460 enclosure with board stack, PROFIBUS PA communication, DC power, NPT cable inlet, approval option A, no process connection	L) A5E02212429

¹⁾ Available with no pressure rating, 0.5 bar g maximum.

Please contact nacc.smpi@siemens.com for special requests.

C) Subject to export regulations AL: N, ECCN: EAR99

F) Subject to export regulations AL: 91999, ECCN: N

L) Subject to export regulations AL: N, ECCN: 3A991X