

## Selection and Ordering data

Order No.

### *Accessories*

#### **SIWAREX JB junction box, stainless steel housing**

for connecting up to 4 load cells in parallel

**7MH4710-1EA**

#### **SIWAREX JB junction box, stainless steel housing, ATEX**

For the parallel switching of up to 4 load cells

Explosion protection for zones 1, 2, 20, 21 and 22

**7MH4710-1EA01**

### *Cable (optional)*

#### **Cable Li2Y 1 x 2 x 0,75 ST + 2 x (2 x 0,34 ST) - CY, orange sheath**

to connect SIWAREX U, CS, MS, FTA, FTC and CF to the junction box (JB), extension box (EB) or Ex interface (Ex-I) or between two JB's, for fixed laying, occasional bending permitted, 10.8 mm (0.43 inch) outer diameter, for ambient temperature -40 to +80 °C (-40 ... +176 °F)

**7MH4702-8AG**

#### **Cable Li2Y 1 x 2 x 0.75 ST + 2 x (2 x 0.34 ST) - CY, blue sheath**

to connect the junction box (JB) or extension box (EB) in a potentially explosive atmosphere to the Ex interface (Ex-I), for fixed laying, occasional bending permitted, blue PVC insulating sheath, approx. 10.8 mm (0.43 inch) outer diameter, for ambient temperature -40 ... +80 °C (-40 ... +176 °F)

**7MH4702-8AF**