





## Technical specifications

Type		 N 148/21	 N 146	 N 350E	 N 151
<b>Enclosure data</b>					
Design		N	N	N	N
Modular installation devices for mounting on TH35 EN 60715 mounting rail		✓	✓	✓	✓
Width (1 MW = 18 mm)		2 MW	2 MW	4 MW	4 MW
<b>Display/control elements</b>					
LEDs for indicating that the device is ready-to-run, KNX communication, IP communication		✓	✓	✓	✓
LCD		--	--	✓	--
<b>Power supply</b>					
Electronics powered via an external AC/DC power supply unit	V	12 ... 30	12 ... 30	12 ... 30	12 ... 30
<b>Bus connection</b>					
Integrated bus coupling units		✓	✓	✓	✓
Bus connection via bus terminal		✓	✓	✓	✓
<b>Mains connection</b>					
Ethernet connection via RJ45 socket		✓	✓	✓	✓
Plug-in terminal block for the connection of an external power supply unit		✓	✓	✓	--
<b>Gateway</b>					
Supports KNXnet/IP		✓	✓	✓	✓
Line coupler function		--	✓	--	--
Interface functions		✓	✓	✓ <sup>1)</sup>	✓ <sup>1)</sup>
Integrated real-time clock weekly scheduling program for 100 scheduled entries/Astro function		--	--	✓	--
Yearly time switching functions		--	--	✓	--
Event entries		--	--	200	--
Logic gates		--	--	30	--
Web servers		--	--	--	✓

1) ETS3 and visualization.