

| Selection and Ordering data | Order code | | | |
|---|---------------------------------|-----------------------|-----------------------|-----------------------|
| <i>Further designs</i> | | HART | PA | FF |
| Add "-Z" to Order No. and specify Order Code. | | | | |
| Cable socket for M12 plug • metal • Stainless steel | A50 A51 | | ✓ ✓ | ✓ ✓ |
| Rating plate inscription (instead of English) • German • French • Spanish • Italian English rating plate Pressure units in inH ₂ O and/or psi | B10 B12 B13 B14 B21 | ✓ ✓ ✓ ✓ ✓ | ✓ ✓ ✓ ✓ ✓ | ✓ ✓ ✓ ✓ ✓ |
| Quality inspection certificate (factory calibration) to IEC 60770-2 | C11 | ✓ | ✓ | ✓ |
| Inspection certificate Acc. to EN 10204-3.1 | C12 | ✓ | ✓ | ✓ |
| Factory certificate Acc. to EN 10204-2.2 | C14 | ✓ | ✓ | ✓ |
| Set output signal to upper limit of 22.0mA | D05 | ✓ | ✓ | ✓ |
| Degree of protection IP68 (only for M20x1.5 and ½-14 NPT) | D12 | ✓ | ✓ | ✓ |
| Mounting • Weldable sockets for standard 1½" threaded connection • Weldable socket for minibolt connection 1" (incl. screw 5/16-18 UNC-2B and washer) | P01 P02 | ✓ ✓ | ✓ ✓ | ✓ ✓ |
| Additional data Please add "-Z" to Order No. and specify Order code(s) and plain text. | | | | |
| Measuring range to be set Specify in plain text (max. 5 characters): Y01: ... up to ... mbar, bar, kPa, MPa, psi | Y01 | ✓ | | |
| Stainless steel tag plate (measuring point description) Max. 16 char., specify in plain text: Y15: | Y15 | ✓ | ✓ | ✓ |
| Measuring point text Max. 27 char., specify in plain text: Y16: | Y16 | ✓ | ✓ | ✓ |
| Entry of HART address (TAG) Max. 8 char., specify in plain text: Y17: | Y17 | ✓ | | |
| Setting of pressure indication in pressure units Specify in plain text (standard setting: bar): Y21: mbar, bar, kPa, MPa, psi, ... Note: The following pressure units can be selected: bar, mbar, mm H ₂ O [*] , inH ₂ O [*] , ftH ₂ O [*] , mmHG, inHG, psi, Pa, kPa, MPa, g/cm ² , kg/cm ² , Torr, ATM or % *) ref. temperature 20 °C | Y21 | ✓ | ✓ | ✓ |
| Setting of pressure indication in non-pressure units⁵⁾ Specify in plain text: Y22: up to l, m ³ , m, USg, ... (specification of measuring range in pressure units "Y01" is essential, unit with max. 5 characters) | Y22 + Y01 | ✓ | | |
| Preset bus address possible between 1 and 126 Specify in plain text: Y25: Only "Y01" and "Y21" can be factory preset | Y25 | | ✓ | |

✓ = available