

Selection and Ordering data

Order No.

SIWAREX WL280 RN-S SA load cell**7MH5113-**Stainless steel, low mounting height, IP66/68 accuracy class C3 acc. to OIML R60¹⁾**D 0****Rated load****Cable length**

• 60 kg (132.28 lb)	3 m (9.84 ft)	2 Q
• 130 kg (286.60 lb)	3 m (9.84 ft)	3 D
• 280 kg (617.29 lb)	3 m (9.84 ft)	3 J
• 500 kg (1102.31 lb)	3 m (9.84 ft)	3 P
• 1 t (0.98 tn. L.)	3 m (9.84 ft)	4 A
• 2 t (1.97 tn. L.)	6 m (19.68 ft)	4 G
• 3.5 t (3.44 tn. L.)	6 m (19.68 ft)	4 L
• 5 t (4.92 tn. L.)	6 m (19.68 ft)	4 P
• 10 t (9.84 tn. L.)	15 m (49.21 ft)	5 A
• 13 t (12.79 tn. L.)	15 m (49.21 ft)	5 D
• 28 t (27.56 tn. L.)	15 m (49.21 ft)	5 J
• 60 t (59.05 tn. L.)	15 m (49.21 ft)	5 Q

Explosion protection²⁾

Without

0

Explosion protection for zones 1, 2, 20, 21, 22

1

1) OIML R60 test certificate available soon

2) ATEX certification available soon