

| Selection and Ordering data   | Order No.  |
|---|--|
| <b>Multiway cock PN 100 (1450 psi)</b><br>for flanging to pressure transmitters, weight 2.5 kg (without accessory set), without certificate | <b>7MF9004 - ■■A</b><br><br><b>1P</b><br><br><b>1Q</b> |
| For water and non-aggressive gases and vapors   |  |
| For aggressive liquids, gases and vapors  |  |
| <b>Accessories</b>  |  |
| Factory test certificate EN 10204-2.2<br>Material acceptance test certificate EN 10204-3.1  | <b>7MF9000-8AB</b><br><b>7MF9000-8AD</b>               |

| Selection and Ordering data  | Order code               | Order No.                                |
|--|--------------------------|--|
| <b>Further designs<sup>1)</sup></b><br>Please add "-Z" to Order No. and specify Order code.  |                          |  |
| <b>Accessory set to EN</b><br>(required for flanging, weight 0.2 kg)<br>4x screws $\frac{7}{16}$ -20 UNF x 1 inch to ASME B18.2.1; chromized steel<br>2x gaskets made of PTFE, max. permissible temperature 80 °C (176 °F)   | <b>L31</b>               | <b>7MF9004-5CC</b>                       |
| <b>Accessory set to DIN</b><br>(required for flanging, weight 0.2 kg)<br>4x screws M10x25 to DIN EN 24017; chromized steel<br>4x washers Ø 10.5 mm to DIN 125; 2x gaskets made of PTFE, max. permissible temperature 80 °C (176 °F)  | <b>L11</b><br><b>L15</b> | <b>7MF9004-6AD</b><br><b>7MF9004-6AE</b> |
| <b>Multiway cock in oil-free and grease-free design</b><br><br>Oil- and grease-free cleaning for oxygen applications, max. pressure PN 100 (1450 psi) and max. temperature 60 °C (140 °F), BAM-tested lubricant, gasket suitable for oxygen measurement (only with Order No. 7MF9004-1Q.Z) | <b>S11</b>               |  |
| <b>Mounting bracket</b><br>Required <b>for wall mounting</b> or for securing on rack (72 mm grid), made of electrogalvanized sheet-steel, weight 0.85 kg   | <b>M13</b>               | <b>7MF9004-6AA</b>                       |

<sup>1)</sup> When ordering accessory set or mounting together with the multiway cock, please use Order code; otherwise use Order No.