

Selection and Ordering data

Order No.

Valve manifold combination DN 5/DN 8 for vapors**7MF9416-6** **A**

For flanging to pressure transmitters for differential pressure, max. working pressure 420 bar (6092 psi), also available in stainless steel on request (order accessory set with Order code), without certificate

- without test connection
- with test connection M20 x 1.5

C
D**Accessories**

Factory test certificate EN 10204-2.2

7MF9000-8AB

Material acceptance test certificate EN 10204-3.1

7MF9000-8AD**Selection and Ordering data**

Order code

Order No.

Further designs¹⁾

Please add "-Z" to Order No. and specify Order code.

Accessory set to EN

(required for flanging, weight 0.2 kg)

4x screws $7/16$ -20 UNF x $2\frac{1}{8}$ inch to ASME B18.2; chromized steel
2x O-rings to DIN 3771, 20 x 2.65 - S - FPM90, max. permissible 420 bar (6092 psi), 120 °C (248 °F)

B34**7MF9410-5CA****Accessory set to DIN²⁾**

(required for flanging, weight 0.2 kg)

4x screws M10x55 to DIN EN 24014; chromized steel
4x washers Ø 10.5 mm to DIN 125;
2x O-rings to DIN 3771, 20 x 2.65 - S - FPM90, max. permissible 420 bar (6092 psi), 120 °C (248 °F); Flange connection to DIN 19213 only permissible up to PN 160!

B16**7MF9010-6CC**

¹⁾ When ordering accessory set together with the valve manifold combination, please use Order code; otherwise use Order No.

²⁾ Flange connections to DIN 19213 only permissible up to PN 160 (2321 psi)