


Selection and Ordering data	Order No.
SITRANS F C Flow sensors	
SITRANS FCS200 sensor, without heating jacket	7ME4500 - 
Sensor size and material	
DN 10, Hastelloy C22/2.4602	2 D
DN 15, Hastelloy C22/2.4602	2 E
DN 25, Stainless steel AISI 316Ti/1.4571	1 F
Pressure	
PN 214 (DN 25)	K
PN 350 (DN 10 and DN 15)	N
Process connection/flange	
½"/VCO	7 1
¾"/VCO	7 2
1"/VCO	7 3
¼"/NPT pipe thread	8 1
½"/NPT pipe thread	8 2
¾"/NPT pipe thread	8 3
1"/NPT pipe thread	8 4
1½"/NPT pipe thread	8 5
Configuration	
Standard	1
Transmitter	
None	A
Cable	
No cable	A
Calibration	
Standard calibration	1

Selection and Ordering data	Order code
Additional information	
Please add "-Z" to Order No. and specify Order code(s) and plain text.	
Pressure testing certificate PED: 97/23/EC	C11
Material certificate EN 10204-3.1	C12
NDT-Penetrant inspection report ISO 3452	C13
Factory certificate according to EN 10204 2.2	C14
Factory certificate according to EN 10204 2.1	C15
Tag name plate, stainless steel	Y17

Accessories

Description	Order No.
Cable with multiple plug	5 m (16.4 ft) FDK-083H3015
Standard blue cable between	10 m (32.8 ft) FDK-083H3016
SiFLOW FC070/MASS 6000 and FCS200,	25 m (82 ft) FDK-083H3017
5 x 2 x 0.34 mm ² twisted and screened in pairs.	50 m (164 ft) FDK-083H3018
Temperature range -20 °C ... +110 °C (-4 °F ... +230 °F)	75 m (246 ft) FDK-083H3054
	150 m (492 ft) FDK-083H3055

Spare parts

Description	Order No.
Multiple plug for cable mounting	FDK-083H5056
2 kB SENSORPROM unit (Sensor Serial No. and Order No. must be specified by ordering)	FDK-083H4410