					Selection and Ordering data	0.00.	vo. Order code
Description		Orde	er No		SITRANS F C flow sensors		
Cables from MC2 sensor to MASS 6000 tran	smitter				MC2 for Hygienic applications only	7 ME 4	3 1 0 -
10 m (32.8 ft)		FDK	-083I	13001			
25 m (82 ft)		FDK	-083F	13002	Cable		
75 m (246 ft)		FDK	-083F	13003	No cable (see accessories)		A
150 m (492 ft)		FDK	-083I	13004	Calibration	_	
Spare parts					Standard		1
Description		Orde	er No.		- Matched pair		2
2 kB SENSORPROM unit		FDK	-083F	14410	1) Extended density and fraction not possible with	DN 150.	
(Sensor Serial No. and Order No. must be spe at ordering)	cified				Please also see www.siemens.com/SITRA	NSForde	erina
Connection board/PCB		Δ5F	03004	1110	for practical examples of ordering		J
Connection Board/1 CD		AJL	0000-	*110			
					Selection and Ordering data		Order code
Selection and Ordering data	Order	No.	Orde	er code	Additional information		
SITRANS F C flow sensors					Please add "-Z" to Order No. and specify Order	er	
MC2 for Hygienic applications only	7 M E 4				code(s) and plain text.		
					Pressure testing certificate PED: 97/23/EC		C11
Nominal diameter					Material certificate EN 10204-3.1		C12
AISI 316L/1.4435					Welding certificate NDT X-ray: EN 25817/B		C13
DN 20	1 A				Factory certificate according to EN 10204 2.2		C14
DN 25 DN 40	1 B 1 C				Factory certificate according to EN 10204 2.1		C15
					Tag name plate, stainless steel		Y17
DN 50 DN 65	1 D 1 E				Tag name plate, plastic		Y18
DN 80	1 F				Customer-specific transmitter setup		Y20
Nominal pressure 40 bar, PN 25					Customer-specified, matched pair (5 x 2)		Y60
Clamps/screwed-connections	F				Customer-specified calibration (5 x 2)		Y61
Pressure and Process connections							
Dairy screwed connection to DIN 11851					Customer-specified, matched pair (10 x 1)		Y62
DN 20, PN 25	4	0			Customer-specified calibration (10 x 1)		Y63
DN 25, PN 25		1			Special version		Y99
DN 40, PN 25		2					
DN 50, PN 25 DN 65, PN 25		1 3 1 4			Accessories		
DN 80, PN 25		5			Description	C	Order No.
Dairy clamp connectors for DIN 32676					Cables from MC2 sensor to MASS 6000 trans	smitter	
Tri-clamp					10 m (32.8 ft)	F	DK-083H3001
20 mm clamp		7			25 m (82 ft)	F	DK-083H3002
26 mm clamp		8			75 m (246 ft)	F	DK-083H3003
38 mm clamp 50 mm clamp		5 4 5 0			150 m (492 ft)	F	DK-083H3004
66 mm clamp		5 1			, ,		
31 mm clamp	5	5 2					
Aseptic connectors DIN 11864-2 Form A for					Spare parts		
DIN tubes					Description	C	Order No.
DN 20 DN 25		5 8 5 7			2 kB SENSORPROM unit	F	DK-083H4410
DN 40		6 0			(Sensor Serial No. and Order No. must be spe by ordering)	cified	
DN 50		61			sy stasting)		
DN 65		6 2					
DN 80	6	3					
Configuration							
Flow and density (5 kg/m <sup>3</sup> ) Flow, BRIX/PLATO and density (1 kg/m <sup>3</sup> ) <sup>1)</sup>			1 2				
Density (1 kg/m <sup>3</sup> ) <sup>1)</sup>			5				
Flow, fraction (customer-specified application			9	NOY			
from the net)							
Ex-approval							
Standard, without explosion protection			Α				

Selection and Ordering data

Order No. Order code

Accessories