


F US SONOFLO spare parts


Spare parts

Description	Order No.
Wall mounting kit for 7ME3150-1AA10-1AA0 and 7ME3150-1AA20-1AA0, using 4 x coaxial sensor cables, wall brackets, PG 13.5 cable glands.	FDK:085F5027




SENSORPROM memory unit for sensors with SONO 3000 transmitters

Description	Order No.
SENSORPROM memory unit for SITRANS F US systems with transmitter type SONO 3000 When ordering: Inform on sensor Order No. and Serial No.	FDK:085B5329




Terminal housing with PG 13.5 cable glands

Type	Order No.
Material: PA 6.6, Temperature range: -20 ... +100 °C (-4 ... +212 °F)	FDK:085B1403
Material: AISI 316, Temperature range: -20 ... +200 °C (-4 ... +392 °F)	FDK:085B1402








SONO 3200 spare parts, complete units

Type	Material	Gasket rating	Pressure rating	Terminal housing/ cable gland	Approv.	Temp. range [°C (°F)]	Length mm (inch)	Order No.
Flange	316 SS	Graphite	PN 40	316 SS/M20		-20 ... +200 (-4 ... +392)	158 (6.22)	On request






Spare parts for transmitter SONO 3000

Description	Order No.	Description	Order No.
SONO 3000 19" back print for IP65 (NEMA 4) wall mounting 230 V version	FDK:085F5327	SONO 3000 EEx d, front glas incl. frame	FDK:085U2109
SONO 3000 assembly plate for coaxial connection in the SONO 3300 sensor and wall mounting connection box	FDK:085L1023	SONO 3000 EEx d, gaskets for transmitter housing	FDK:085U2002
SONO 3000 assembly base plate	FDK:085L1015	Connection kit SONO 3300 / FUS060	On request
		Coaxial cable with transducer connection for sensor type SONO 3300-CT (1 pc.)	
		1 x 10 m (32.8 ft)	FDK:085L2400
		1 x 20 m (65.6 ft)	FDK:085L2401
		1 x 30 m (98.4 ft)	FDK:085L2402








SONO 3200 / SONO 3000 PG 13.5 cable glands (each 1 pc.)

Type	Material	Temperature range [°C (°F)]	Approval	Order No.	
PG 13.5	Nickel-plated brass, cable Ø 6 ... 8 mm	-20 ... +100 (-4 ... +212)		A5E02247692	
PG 13.5	Stainless steel, cable Ø 5 ... 6 mm	-20 ... +200 (-4 ... +392)		A5E02247682	
PG 13.5	Stainless steel, cable Ø 6 ... 8 mm	-20 ... +200 (-4 ... +392)	Ex d ¹⁾	A5E02247711	

¹⁾ No ATEX

Cables

Description	Order No.	
Standard 75 Ω coaxial cable T _{max} = 75 °C (167 °F)		
• 15 m (49.2 ft)	FDK:085B1373	
• 30 m (98.4 ft)	FDK:085B1374	
• 60 m (196.8 ft)	FDK:085B1375	
• 100 m (328 ft)	FDK:085B1376	
Teflon 75 Ω coaxial cable T _{max} = 200 °C (392 °F)		
• 15 m (49.2 ft)	FDK:085B1378	
• 30 m (98.4 ft)	FDK:085B1379	