

**SITRANS FUT1010 (Liquid)**

K) 7 ME362 - - 0

**Transmitter type**

- No Transmitter
- IP65 NEMA 4X (2 path)
- IP65 NEMA 4X (2 path) with MODBUS
- IP65 NEMA 4X (3 or 4 path)
- IP65 NEMA 4X (3 or 4 path) with MODBUS
- IP66 NEMA 7 wall mount/explosionproof (2 Path)
- P66 NEMA 7 wall mount/explosionproof (2 Path) with MODBUS
- P66 NEMA 7 wall mount/explosionproof (3 or 4 Path)
- P66 NEMA 7 wall mount/explosionproof (3 or 4 Path) lwith MODBUS

0  
1  
2  
3  
4  
5  
6  
7  
8

**Input power**

- 90 ... 240 V AC
- 9 ... 36 V DC

1  
2

**Number of ultrasonic paths**

- 2 path
- 3 path
- 4 path

B  
C  
D

**Pipe size**

- DN 100 (4") (Dual Path only)
- DN 150 (6")(Dual Path only)
- DN 200 (8")
- DN 250 (10")
- DN 300 (12")
- DN 400 (16")
- DN 450 (18")
- DN 500 (20")
- DN 600 (24")

A  
B  
C  
D  
E  
B  
G  
H  
J

**Flange rating**

- Class 150 (Raised Face)
- Class 300 (Raised Face)
- Class 600 (Raised Face)

0  
1  
2

**Upstream/downstream meter run**

- None
- 10 pipe diameter upstream Tube only
- 10 pipe diameter upstream Tube with flow conditioner
- 5 pipe diameter downstream tube only
- 10D up and 5D downstream tubes
- 10D up and 5D downstream tubes with flow conditioner

0  
1  
2  
3  
4  
5

**Liquid type range (select closest match)**

- Water
- Multiple Crude Oils
- Light Crude only
- Heavy Crude only
- Multiple Finished Products
- Gasolines Only
- Kerosene
- Jet Fuel
- Diesel
- Multiple Fuel Oils
- Heavy Fuel Oils
- Liquified Gases

A  
B  
C  
D  
E  
F  
G  
H  
J  
K  
L  
M

**Liquid temperature range**

- 28 ... +65 °C (-20 ... +150 °F )
- 1 ... 93 °C (30 ... 200 °F)

A  
B

**Transmitter and sensor approval**

- FM/CSA, CE
- ATEX and PED, CE, C-TICK
- INMETRO

1  
2  
3

K) Subject to export regulations AL: N, ECCN: 5A991X.

**Selection and Ordering data**

Order code

**Further designs**

Please add "-Z" to Order No. and specify Order code(s).

Cable assembly for flow sensor (add one K.. per flow path)

- Cable and termination for one sensor path (see "Sensor cable chart for options")

**K..**

- Termination for user supplied cable

**T01**

Cable assembly for temperature sensor (only 1 required)

- Cable and termination for temperature sensor (see "Transducer cable chart for options").

**R..**

- Termination for user supplied RTD cable

**T31**Wet flow transfer calibration (priced for 1 pipe calibration)  
Requires completion of calibration form

- 6 point for DN 100 (4 inch)
- 6 point for DN 125 to DN 200 (5 to 8 inch)
- 6 point for DN 250 to DN 300 (10 to 12 inch)
- 6 point for DN 350 to DN 400 (14 to 16 inch)
- 6 point for DN 450 to DN 500 (18 to 20 inch)
- 6 point for DN 550 to DN 600 (22 to 24 inch)

**D10****D11****D12****D13****D14****D15**

Tag name plate

- Stainless steel tags with 3.2 mm (0.13 inch) character size (68 characters max.)

**Y19****Selection and Ordering data**

Order No.

**Operating Instructions for SITRANS FUT1010 (Liquid)**

English NEMA 4X wall mount &amp; NEMA 7 wall mount explosionproof

**A5E02639184**

German NEMA 4X wall mount &amp; NEMA 7 wall mount explosionproof

**A5E03086468**

This device is shipped with a Quick Start Guide and a CD containing further SITRANS F literature.

All literature is also available for free at:

<http://www.siemens.com/flowdocumentation>

**SITRANS FUT1010 (Gas)**

K) **7 ME3 63** - - - - - **0** - - - - -

**Transmitter type**

- No meter
- IP65 NEMA 4X (2 path)
- IP65 NEMA 4X (2 path) with MODBUS
- IP65 NEMA 4X (3 or 4 path)
- IP65 NEMA 4X (3 or 4 path) with MODBUS
- IP66 NEMA 7 wall mount flame/explosion proof (2 Path)
- IP66 NEMA 7 wall mount flame/explosion proof (2 Path) with MODBUS
- IP66 NEMA 7 wall mount flame/explosion proof (3 or 4 Path)
- IP66 NEMA 7 wall mount flame/explosion proof (3 or 4 Path) with MODBUS

0  
1  
2  
3  
4  
5  
6  
7  
8

**Input power**

- 90 ... 240 V AC
- 9 ... 36 V DC

1  
2

**Number of ultrasonic paths**

- 2 path (standard enclosure material)
- 3 path (standard material)
- 4 path (standard material)

B  
C  
D

**Pipe size**

- DN 100 (4") (Dual Path only)
- DN 150 (6")(Dual Path only)
- DN 200 (8")
- DN 250 (10")
- DN 300 (12")
- DN 400 (16")
- DN 450 (18")
- DN 500 (20")
- DN 600 (24")

A  
B  
C  
D  
E  
G  
H  
J

**Flange rating**

- Class 300 (Raised Face)
- Class 600 (Raised Face)

1  
2

**Upstream/downstream meter run**

- None
- 10 pipe diameter upstream Tube only
- 10 pipe diameter upstream Tube with flow conditioner
- 5 pipe diameter downstream tube only
- 10D up and 5D downstream tubes
- 10D up and 5D downstream tubes with flow conditioner

0  
1  
2  
3  
4  
5

**Gas type range (select closest match)**

- Natural Gas (mostly CH<sub>4</sub>)
- Process Gases (N<sub>2</sub>, O<sub>2</sub>, CO, Ar)
- Helium
- Hydrogen

A  
B  
C  
D

**Gas temperature zange**

- 28 ... +65 °C (-20 ... +150 °F )
- 1 ... 93 °C (30 ... 200 °F)

A  
B

**Transmitter and sensor approval**

- FM/CSA, CE
- ATEX and PED, CE, C-TICK
- INMETRO

1  
2  
3

K) Subject to export regulations AL: N, ECCN: 5A991X.

**Selection and Ordering data**

Order code

**Further designs**Please add **"-Z"** to Order No. and specify Order code(s).

Cable assembly for flow sensor (Add one K.. per flow path)

- Cable and termination for one sensor path (see "Transducer cable chart for options")
- Termination for user supplied cable

**K..****T01**

Cable assembly for temperature sensor (only 1 required)

- Cable and termination for temperature sensor (see "Transducer cable chart for options").
- Termination for user supplied RTD cable

**R..****T31**Wet flow transfer calibration (priced for 1 pipe calibration)  
Requires completion of calibration form

- 6 point for DN 100 (4 inch)
- 6 point for DN 125 to DN 200 (5 to 8 inch)
- 6 point for DN 250 to DN 300 (10 to 12 inch)
- 6 point for DN 350 to DN 400 (14 to 16 inch)
- 6 point for DN 450 to DN 500 (18 to 20 inch)
- 6 point for DN 550 to DN 600 (22 to 24 inch)

**D10****D11****D12****D13****D14****D15**

Tag name plate

- Stainless steel tags with 3.2 mm (0.13 inch) character size (68 characters max.)

**Y19****Selection and Ordering data**

Order No.

**Operating Instructions for SITRANS FUG1010**

English NEMA 4X wall mount &amp; NEMA 7 wall mount explosionproof

**A5E02639185**

German NEMA 4X wall mount &amp; NEMA 7 wall mount explosionproof

**A5E03086485**

This device is shipped with a Quick Start Guide and a CD containing further SITRANS F literature.

All literature is also available for free at:

<http://www.siemens.com/flowdocumentation>