Selection and ordering data	Order No.	
OXYMAT 6 gas analyzer D 19" rack unit for installation in cabinets D) 7MB2021- 0 -	Cannot be combined
Gas connections Pipe with 6 mm outer diameter Pipe with ¼" outer diameter	0	
Smallest possible span O2 0.5 % reference gas pressure 3 000 hPa 0.5 % reference gas pressure 100 hPa (external pump) 2 % reference gas pressure 3 000 hPa	A B C	A E30 B B B E30, Y02
2 % reference gas pressure 100 hPa (external pump) 5% reference gas pressure 3 000 hPa 5% reference gas pressure 100 hPa (external pump)	D E F	$\begin{array}{cccc} D & D & D \longrightarrow E30, Y02 \\ & \\ F & F & F \longrightarrow E30, Y02 \end{array}$
Sample chamber Non-flow-type compensation branch • Made of stainless steel, mat. no. 1.4571 • Made of tantalum Flow-type compensation branch • Made of stainless steel, mat. no. 1.4571 • Made of tantalum	A B C D	C
Internal gas paths Hose made of FKM (Viton) Pipe made of titanium Pipe made of stainless steel, mat. no. 1.4571	0 1 2	1 1 <u>→ Y02</u>
Power supply 100 120 V AC, 48 63 Hz 200 240 V AC, 48 63 Hz	0 1	
Monitoring (reference gas, sample gas) Without Reference gas only Reference gas and sample gas (with flow indicator and pressure switch for sample gas) Sample gas only	A B C D	$\begin{vmatrix} \\ B \\ C \\ C$
Add-on electronics Without AUTOCAL function • With 8 additional binary inputs/outputs • With serial interface for the automotive industry (AK) • With 8 additional binary inputs/outputs and PROFIBUS PA interface • With 8 additional binary inputs/outputs and PROFIBUS DP interface	A B D E F	D → E20
Language German English French Spanish Italian	- 0 1 2 3 4	
Additional versions	Order code	Cannot be combined
Add "-Z" to Order No. and specify order codes.		
Telescopic rails (2 units) Kalrez gaskets in sample gas path TAG labels (specific inscription based on customer information)	A31 B01 B03	
FM/CSA certificate – Class I Div 2 ATEX II G certificate; safety-related measurements in non-hazardous gas zone Clean for O ₂ service (specially cleaned gas path)	E20 E30 Y02	→ E30 → E20
Measuring range indication in plain text, if different from the standard setting	Y11	

D) Subject to export regulations AL: 91999, ECCN: N

Selection and ordering data

Retrofitting sets		Order No.
RS 485/Ethernet converter		A5E00852383
RS 485/RS 232 converter		C79451-Z1589-U1
RS 485/USB converter	D)	A5E00852382
AUTOCAL function with serial interface for the automotive industry (AK)		C79451-A3480-D512
AUTOCAL function with 8 binary inputs/outputs		C79451-A3480-D511
AUTOCAL function with 8 binary inputs/outputs and PROFIBUS PA		A5E00057307
AUTOCAL function with 8 binary inputs/outputs and PROFIBUS DP		A5E00057312
D) Subject to export regulations AL: 91999, ECCN: N		