

The data for series 1LA8 with type of protection “n” or protection against dust explosions can be found in the selection and ordering data in catalog part 3 “Non-standard motors of frame size 315 and above”. The technical specifications are identical to the specifications of the non-explosion-proof versions. They are or-

dered using additional order options (special versions). These special versions for voltages, construction types or options are listed in part “Non-standard motors frame size 315 and above”.

### Special versions according to ATEX

Motor type		Zone 2		VIK <sup>1)</sup> (includes Zone 2, utilization 155 (F) according to 130 (B))		Zone 21		Zone 22	
	Frame size	Mains-fed operation Order code <b>M72</b>	Converter-fed operation (FC) Order code <b>M73</b>	Mains-fed operation Order code <b>K30</b>	Converter-fed operation (FC) On request	Mains-fed operation Order code <b>M34</b>	Converter-fed operation (FC) Order code <b>M38</b>	Mains-fed operation Order code <b>M35</b>	Converter-fed operation (FC) Order code <b>M39</b>
1LA8	315	✓	O. R.	✓	O. R.	–	–	✓	✓
	355	✓	O. R.	✓	O. R.	–	–	✓	✓
	400	✓	O. R.	–	–	–	–	✓	✓
	450	✓	O. R.	–	–	–	–	✓	✓

O. R. Possible on request

✓ With additional charge

– Not possible