Selection and Ordering data	Order No.
Operating Instructions - Standard	
English C)	7ML1998-5JH04
German C)	7ML1998-5JH33
Note: The Operating Instructions should be ordered as a separate line on the order.	
Quick Start manual, multi-language C)	7ML1998-5QY83
This device is shipped with the Siemens Milltronics manual CD containing the complete ATEX Quick Start and Operating Instructions library.	
Operating Instructions - Digital	
English C)	7ML1998-5JJ04
French C)	7ML1998-5JJ11
German C)	7ML1998-5JJ33
Note: The Operating Instructions should be ordered as a separate line on the order.	
Quick Start manual, multi-language C)	7ML1998-5XA83
This device is shipped with the Siemens Milltronics manual CD containing the complete ATEX Quick Start and Operating Instructions library.	
Accessories One metallic cable gland M20x1.5, -40 +80 °C (-40 +176 °F) with integrated shield connection (available for PROFIBUS PA) General Purpose	7ML1930-1AQ
1/2" NPT General Purpose Cable Entry IP68/IP69K C) NEMA6, -40100 °C (-40212 °F), cable size 6 12 mm (0.236 0.472") M20x1.5 General Purpose Cable Entry IP68/IP69K C)	A3E03232300
NEMA6,-40100 °C (-40212 °F), cable size 7 12 mm (0.275 0.472") Hazardous Locations	7.020202001
1/2" NPT EMC rated Cable Gland: Dust Ignition Proof, Flameproof Exd, and Increased Safety ATEX II 2 GD ExtD A21 (Zone 1,Zone 2, Zone 21, Zone 22, and in Gas Groups IIA,IIB and IIC) -60 +80 °C IP66,IP67,IP68, NEMA4X, cable sizes 5.5 12 mm (0.216 0.472")	A5E03252527
M20 EMC rated Cable Gland: Dust Ignition Proof, Flameproof Exd, and Increased Safety ATEX II 2 GD ExtD A21 (Zone 1,Zone 2, Zone 21, Zone 22 and in Gas Groups IIA,IIB and IIC) -60 +80 °C IP66,IP67,IP68, NEMA4X, cable sizes 5.5 12 mm (0.216 0.472")	A5E03252528
Blind threaded flanges are available. Please contact ceg.smpi@siemens.com with a completed application data sheet on page 5/14	
Pointek Specials	See page 5/83
C) Subject to export regulations AL: N, ECCN: EAR99	