Selection and Ordering data		Orde	Order No.	
SITRANS F C MASS 6000 transmitter Transmitter Ex d for remote mounting inclusive of			4110-	
wall mounting kit	J	2	- A	
Enclosure				
Ex d SS with 5 m (16.5 ft) cable		G H		
Ex d SS with 10 m (32.8 ft) cable Ex d SS with 25 m (82.0 ft) cable		J		
Output configuration	,			
1 current, 1 frequency, 1 relay		A		
Supply voltage 24V AC/DC			2	
Ex approvals			-	
ATEX			1	
Display/Keypad				
With display			1	
Serial communication				
No communication HART			A B	
PROFIBUS PA Profile 3			F	
FOUNDATION Fieldbus H1			J	
Cable gland				
M20			1	
Operating instructions for SI	TRANS F C MAS	SS 6000	Ex d	
Description	Order No.			
Operating instructions for SITRANS F.C. MASS 6000 Ex. d.				
• English	A5E02944883			
This device is shipped with a Q further SITRANS F literature.	uick Start guide a	nd a CD	containing	
All literature is also available for http://www.siemens.com/flowdo				
Note:				
Only communication modules w	ith Ex approvals a	are allowe	ed.	

Please also see $\underline{www.siemens.com/SITRANSFordering}$ for practical examples of ordering