

Selection and Ordering data	Order No.
SITRANS TF280 WirelessHART Temperature transmitter ▶ D) (Required battery not included with delivery, see accessories)	7MP1110-0A-000
Connections/cable entry Cable gland M20x1.5 ¹⁾ Sensor pipe with Pt100, G½" male thread, pre-mounted and connected	C D
Display Digital display, visible	1
Enclosure Die-cast aluminum	1
Explosion protection Not included	A
Antenna Variable, attached to device	A
Further designs	Order code
Please add "-Z" to Order No. and specify Order code(s) and plain text.	
Measuring point number (TAG Nr.) max. 16 digits entered in plain text Y15:	Y15
Measuring point message max. 27 characters entered in plain text: Y16:	Y16
Accessories	Order No.
Lithium battery for SITRANS TF280/P280 ▶ D)	7MP1990-0AA00
Mounting bracket, steel	7MF4997-1AC
Mounting bracket, stainless steel ▶	7MF4997-1AJ
Cover, die-cast aluminum, without window ▶ F)	7MF4997-1BB
Cover, die-cast aluminum, with window F)	7MF4997-1BE
Thread adapter M20x1.5 (male thread) on ½-14 NP (female thread) ▶	7MP1990-0BA00
Thread adapter M20x1.5 (male thread) on G½B (female thread) ▶	7MP1990-0BB00
IE/WSN-PA Link	see Sec. 9
HART modem with RS232 interface ▶ D)	7MF4997-1DA
HART modem with USB interface ▶	7MF4997-1DB
SIMATIC PDM	see Sec. 9

▶ Available ex stock

1) Please order sensor separately.

D) Subject to export regulations AL:N, ECCN: EAR99H.

F) Subject to export regulations AL:9I999, ECCN: N.