

Selection and Ordering data

Compensation vessel, without certificate

Max. working pressure	Characteristic ¹⁾	Material	Mat. No.	Connections Input	Output	Approx. contents cm ³	Approx. weight kg	Order No.
160 bar	A	16 Mo 3	1.5415	Threaded socket G½, form R, DIN 19207	Threaded socket G½, form V, DIN 19207	250	0.8	7MF9015 - 1 A
250 bar	B	16 Mo 3	1.5415	Welding sleeve Ø 21.3 mm × 6.3 mm	Welding sleeve Ø 21.3 mm × 6.3 mm	250	0.8	1 B
250 bar	B	16 Mo 3	1.5415	Welding sleeve Ø 24 mm × 7.1 mm	Welding sleeve Ø 24 mm × 7.1 mm	250	1	1 C
250 bar	B	11 CrMo 9 10	1.7383	Welding sleeve Ø 24 mm × 7.1 mm	Welding sleeve Ø 24 mm × 7.1 mm	250	1	1 D
250 bar	B	16 Mo 3	1.5415	Welding sleeve Ø 33.7 mm × 4.5 mm	Welding sleeve Ø 24 mm × 7.1 mm	250	0.7	1 E
160 bar	A	16 Mo 3	1.5415	Threaded socket G½, form R, DIN 19207	Threaded socket G½, form V, DIN 19207	20	1.6	5 A
500 bar	D	16 Mo 3	1.5415	Welding sleeve Ø 21.3 mm × 6.3 mm	Welding sleeve Ø 21.3 mm × 6.3 mm	20	1.6	5 B
500 bar	D	16 Mo 3	1.5415	Welding sleeve Ø 24 mm × 7.1 mm	Welding sleeve Ø 24 mm × 7.1 mm	20	1.6	5 C
500 bar	E	11 CrMo 9 10	1.7383	Welding sleeve Ø 24 mm × 7.1 mm	Welding sleeve Ø 24 mm × 7.1 mm	20	1.6	5 D

Accessories

Factory test certificate EN 10204-2.2

Material acceptance test certificate EN 10204-3.1

7MF9000-8AB

7MF9000-8AD

¹⁾ See Figure "Permissible working pressure as a function of the permissible working temperature"