

**Selection and Ordering data**

Order No.

**Oval flange**

with female thread 1/2-14 NPT, max. working pressure 420 bar, flange connection to DIN EN 61518, form A

**Material**

P250GH, mat. No.: 1.0460

**7MF9408-2CE**

X 2 CrNiMo 17 13 2, mat. No. 1.4404/316L

**7MF9408-2CL****Selection and Ordering data**

Order code

Order No.

**Further designs<sup>1)</sup>**

Please add "**-Z**" to Order No. and specify Order code.

**Accessory set to EN**

2x screws 7/16"-20 UNF x 1 1/2 inch to ASME B 18.2.3; chromized steel

**E36****7MF9408-5DA**

1x flat gasket made of PTFE, max. permissible 420 bar, 80 °C

2x screws 7/16"-20 UNF x 1 1/2 inch to ASME B 18.2.3; chromized steel

**E34****7MF9408-5CA**

1x O-ring to DIN 3771, 20 x 2.65 - S - FPM90, max. permissible 420 bar, 120 °C

**Accessory set to DIN**

2x screws M10x40 to DIN EN ISO 4762; chromized steel  
2x washers Ø 10.5 mm to DIN 125;  
1x O-ring to DIN 3771, 20 x 2.65 - S - FPM90,  
max. permissible 420 bar, 120 °C<sup>2)</sup>

**E13****7MF9408-6AA**

2x screws M10x40 to DIN EN ISO 4762; chromized steel  
2x washers Ø 10.5 mm to DIN 125;  
1x flat gasket made of PTFE,  
max. permissible 420 bar, 80 °C<sup>2)</sup>

**E16****7MF9408-6BA**

<sup>1)</sup> When ordering accessory set together with the oval flange, please use Order code; otherwise use Order No.

<sup>2)</sup> Flange connections with M10 screws only permissible up to PN 160