

Adapters G $\frac{1}{2}$

for pressure gauges and shut-off fittings

Nipple connection

G $\frac{1}{2}$ to DIN 16284 (union nut with nipple and gasket); max. working pressure 400 bar; weight 0.1 kg;
 connection: G $\frac{1}{2}$ to DIN EN 837-1;
 Female thread G $\frac{1}{2}$

MaterialMat. No.

CuZn39Pb3

CW 614N

M56340-A0001

Union nut

9 SMn 28 k

1.0715

M56340-A0002

Nipple:

RSt 37-2

1.0037

M56340-A0003

Union nut

X 8 CrNiS 18 9

1.4305

Nipple:

X 6 CrNiMoTi 17 12 2 1.4571/316Ti

Nipple connection

M20 x 1.5 to DIN 16284 (union nut with nipple and gasket); max. working pressure 400 bar; weight 0.1 kg;
 connection: G $\frac{1}{2}$ to DIN EN 837-1;
 Female thread G $\frac{1}{2}$

MaterialMat. No.

Union nut

X 8 CrNiS 18 9

1.4305

M56340-A0008

Nipple:

X 6 CrNiMoTi 17 12 2 1.4571/316Ti

Clamping sleeve

G $\frac{1}{2}$ to DIN 16283; max. working pressure 400 bar; weight 0.1 kg;
 Connections: G $\frac{1}{2}$ to DIN EN 837-1;
 Female thread: G $\frac{1}{2}$ right-hand G $\frac{1}{2}$ left-hand

MaterialMat. No.

CuZn39Pb3

CW614N

M56340-A0004

9 SMn 28 k

1.0715

M56340-A0005**Collar-adapter**

max. working pressure; weight 0.1 kg;
 Connections: G $\frac{1}{2}$ to DIN EN 837-1;
 Male thread: G $\frac{1}{2}$, G $\frac{1}{2}$

MaterialMat. No.

CuZn39Pb3

CW614N

M56340-A0006

9 SMn 28 k

1.0715

M56340-A0007