

Selection and Ordering data	Order No.	
<b>SITRANS F C Flow sensors</b>		
<b>SITRANS FCS200 sensor, without heating jacket</b>	<b>7 ME 4 5 0 0 -</b>	
<b>Sensor size and material</b>		
DN 10, Hastelloy C-22	<b>2 D</b>	
DN 15, Hastelloy C-22	<b>2 E</b>	
DN 25, SS mat. no. 1.4571	<b>1 F</b>	
<b>Pressure</b>		
PN 200	<b>K</b>	
PN 350 (DN 10 and DN 15)	<b>N</b>	
<b>Process connection/flange</b>		
½"/VCO	<b>7 1</b>	
¾"/VCO	<b>7 2</b>	
1"/VCO	<b>7 3</b>	
¼"/NPT pipe thread	<b>8 1</b>	
½"/NPT pipe thread	<b>8 2</b>	
¾"/NPT pipe thread	<b>8 3</b>	
1"/NPT pipe thread	<b>8 4</b>	
1½"/NPT pipe thread	<b>8 5</b>	
<b>Configuration</b>		
Standard	<b>1</b>	
<b>Transmitter</b>		
None	<b>A</b>	
<b>Cable</b>		
No cable	<b>A</b>	
<b>Calibration</b>		
Standard calibration	<b>1</b>	

Selection and Ordering data	Order code
<b>Additional information</b>	
Please add "-Z" to Order No. and specify Order code(s) and plain text.	
Pressure testing certificate PED: 97/23/EC	<b>C11</b>
Material certificate EN 10204-3.1	<b>C12</b>
Welding certificate to EN 287	<b>C13</b>
Factory certificate according to EN 10204 2.2	<b>C14</b>
Factory certificate according to EN 10204 2.1	<b>C15</b>
Tag name plate, stainless steel	<b>Y17</b>

### Spare parts

Description	Order No.
<b>Multiple plug for cable mounting</b>	<b>FDK-083H5056</b>
<b>Cable with multiple plug</b>	
5 m (16.4 ft)	<b>FDK-083H3015</b>
Standard blue cable between MASS 6000 and MASS 2100,	10 m (32.8 ft) <b>FDK-083H3016</b>
5 x 2 x 0.34 mm <sup>2</sup> twisted and screened	25 m (82 ft) <b>FDK-083H3017</b>
in pairs.	50 m (164 ft) <b>FDK-083H3018</b>
Temperature range -20 °C ... +110 °C	75 m (246 ft) <b>FDK-083H3054</b>
(-4 °F ... +230 °F)	150 m (492 ft) <b>FDK-083H3055</b>
<b>2 kB SENSORPROM unit</b>	<b>FDK-083H4410</b>
(Sensor Serial No. and Order No. must be specified by ordering)	
<b>Bracket</b>	<b>A5E02590427</b>